

Additive blends & packages

| Product | Chem. description | Features and Benefits |
|-------------------------------|--|---|
| KX1200 | Combination of Anti Wear-, Corrosion Protection Additives and Antioxidants | Ashless, for synthetic oils. Excellent antioxidation properties, good antiwear and anticorrosion performance, excellent solubility in mineral and synthetic base stocks. |
| KX1301 | Combination of Anti Wear-, Corrosion Protection Additives and Antioxidants | Ashless, multifunctional. Excellent AO and anticorrosion performance in Group III. Excellent AO properties (>1000 minutes RPVOT at 0.7%) >10.000 h TOST, low sludge. |
| KX1323 | Combination of Anti Wear-, Corrosion Protection Additives and Antioxidants | Biodegradable (EEL) gear oil package. Excellent AW and anti-corrosion performance. Good antioxidation properties. Excellent solubility in synthetic base stocks. |
| NA-LUBE® BL-1208 | Combination of Antioxidants and Corrosion Inhibitors | Biodegradable (EEL) gear oil package. Excellent AW and anti-corrosion performance. Good antioxidation properties. Excellent solubility in synthetic base stocks. |
| NA-LUBE® BL-1232EL | Combination of Anti Wear-, Corrosion Protection Additives and Antioxidants | Ashless, multifunctional. Ready biodegradable (EEL). Good AW, AO (RPVOT & dry TOST) properties. Good SRE-NBR seal compatibility. |
| NA-LUBE® BL-1300FG | Combination of Anti Wear-, Corrosion Protection Additives and Antioxidants | Food grade approved. Very good oxidation thermal and hydrolytic stability. Good antiwear and anticorrosion performance. Passes the Vickers Vane Pump test (V 104-C). |
| NA-LUBE® BL-1400 | Combination of Anti Wear-, Corrosion Protection Additives and Antioxidants | Ashless hydraulic fluid package, low treat rate. Very high oxidation stability, high load carrying capacity. Good demulsification, excellent thermal/hydrolytic stability. Meets Parker Hannifin Denison, SEB, U.S. Steel, AFNOR, VDMA, also VDL. |
| NA-LUBE® BL-1792 | Combination of Anti Wear-, Corrosion Protection Additives and Antioxidants | Ashless pack for slideway applications. Excellent friction control at a low treat level. Good compatibility (de-emulsification). Fully tested in collaboration with SKC. |