

| Products | Description | Application |
|-----------------------|---|--|
| LUVOTIX® R | Castor oil derivative | LUVOTIX® R controls the rheology properties of low to medium polar liquid organic systems. It is used as a thickener, thixotropic or anti-settling agent in paints and coatings, adhesives, sealants and putties as well as in oils. LUVOTIX® R is used as a flow and levelling agent in powder coatings. |
| LUVOTIX® R-RF | Castor oil derivative, inorganically modified | LUVOTIX® R-RF is used as a thickener and thixotropic agent in low to medium polar liquid organic systems. It is easy dispersible, improves the formulations workability and has been primarily developed for putties. |
| LUVOTIX® ZR 50 | Castor oil derivative, inorganically modified | LUVOTIX® ZR50 controls the rheology properties of low polar solvent-based and solvent-free formulations, specifically in highly filled coatings, putties and sealants. |
| LUVOTIX® HT | Castor oil derivative, polyamide-modified | LUVOTIX® HT controls the rheology properties of low to medium polar liquid organic systems. It is used as a thickener, thixotropic or anti-settling agent in paints and coatings, adhesives, sealants and putties as well as in oils. In powder coating formulations, LUVOTIX® HT serves as a levelling agent. |
| LUVOTIX® HT-SF | Castor oil derivative, polyamide-modified | LUVOTIX® HT-SF describes the same application profile as LUVOTIX® HT with an easier activation. |
| LUVOTIX® ZH 5 | Castor oil derivative, polyamide-modified, with inorganic content | LUVOTIX® ZH5 controls the rheology properties of medium to higher polar solvent-based formulations. The material is free-flowing, easily dispersible and particularly suitable for highly filled systems. |
| LUVOTIX® ZH 50 | Castor oil derivative, polyamide-modified, with inorganic content | LUVOTIX® ZH50 controls the rheology properties of medium to higher polar liquid organic systems, specifically in highly filled formulations. |
| LUVOTIX® HP | Polyamide | LUVOTIX® HP is used in solvent-based and solvent-free medium to higher polar liquid organic systems. It is suitable as a thickener, thixotropic or anti-settling-agent in paints and coatings, adhesives, sealants, putties and other formulations. |
| LUVOTIX® AB | Blend of polyamides | LUVOTIX® AB is used in solvent-based and solvent-free medium polar liquid organic systems. Its optimum performance is achieved at process temperatures between 50 and 65°C. It is suitable for highly filled and gloss systems. It is used in paints and coatings, adhesives as well as in sealants, putties and other formulations. |

| Products | Description | Application |
|--------------------------|---|--|
| LUVOTIX® SAB | Blend of polyamides | LUVOTIX® SAB is suitable as a rheology additive for many applications in solvent-based and solvent-free formulations. Its optimum performance is achieved at process temperatures in the range of approx. 50-70°C, depending on the polarities in the formulation. LUVOTIX® SAB optimizes the sag-control and anti-settling properties and is particularly recommended for glossy acrylate or polyester based systems. |
| LUVOTIX® PAB | Blend of polyamides | LUVOTIX® PAB is used as a rheology additive in solvent-based and solvent-free medium to higher polar organic systems. Its optimum performance is achieved at process temperatures above 55°C. LUVOTIX® PAB can be used in primers as well as in glossy top-coat systems. It is suitable for industrial coatings, corrosion protection coatings, adhesives, putties and sealants. |
| LUVOTIX® P 100-15 | Polyolefin | LUVOTIX® P100-15 is used to modify the flow behavior in medium to higher polar solvent-based and solvent-free formulations, especially as an efficient anti-settling agent. |
| LUVOTIX® VP031 | Polyolefin/Stearic acid derivative-hybrid | LUVOTIX® VP031 is used in solvent-based and solvent-free high-build coatings, adhesives and sealants. Due to its physical-chemical properties, LUVOTIX® VP031 is particularly easy to incorporate and activate. |
| LUVOTIX® LT1 | Blend of polyamides | LUVOTIX® LT1 can be activated at very low process temperatures, starting at 40°C. It is used in paints and coatings, adhesives and sealants, putties and other formulations. |
| LUVOTIX® TK1 | 2-pack-rheology additive | LUVOTIX® TK1 is used in situ in combination with crosslinker LUVOTIX® CL1. It is suitable for all systems independent of polarity. In topcoats, it is characterized by high gloss and transparency combined with excellent anti-sag properties. |
| LUVOTIX® CL1 | Amino-functional crosslinker | LUVOTIX® CL1 is used as a crosslinker combined in situ with LUVOTIX® TK1 in a mixing ratio 30:100. |
| LUVOTIX® P25X | Polyolefin paste, 25 % in Xylene | LUVOTIX® P25X is used as an anti-settling and sag-control agent in solvent-based formulations. It improves stabilization in zinc-rich primers. |
| LUVOTIX® R400 | Castor oil derivate | LUVOTIX® R400 is used in powder coatings as process additive and flow modifier. |

Products**Description****Application****LUVOTIX® HT400**Castor oil derivate,
polyamide modified

LUVOTIX® HT400 is used in powder coatings as process additive and flow modifier.